

Power Match®, Micro-lite®, Lubrijet® are registered trademarks of BLOUNT EUROPE SA - Oregon Cutting System Division

Accessories for Chainsaws and Pruners - Description of chains



	Chain type	Pitch	Tooth design	Gauge				Bar length
				.043"	.050"	.058"	.063"	
				1.1 mm	1.3 mm	1.5 mm	1.6 mm	
	Micro Chisel	3/8		N143C-K				12" (30 cm)
	Micro Chisel	1/4		E143MC-K				10" (25 cm)
	Micro Chisel	1/4			E650MC-K			up to 16" (40 cm)
	Semi Chisel	3/8 LOW PRO		N143C-K				from 12" to 16" (from 30 to 40 cm)
	Semi Chisel	3/8 LOW PRO			N150C-N			
	Semi Chisel	3/8 LOW PRO			N150C-K			
	Semi Chisel	.325			K250C-N			from 11" to 20" (from 28 to 50 cm)
	Semi Chisel	.325			K250C-K			
	Semi Chisel	.325				K258C-N		
	Semi Chisel	.325				K258C-K		
	Semi Chisel	.325					K263C-N	from 13" to 18" (from 33 to 45 cm)
	Semi Chisel	.325			K250NK-K			
	Chisel	.325			K250L-N	K258L-N	K263L-N	
	Semi Chisel	3/8			A350EP-N			up to 36" (up to 90 cm)
	Semi Chisel	3/8				A358EP-N		
	Semi Chisel	3/8					A363EP-N	
	Pro-Chisel	3/8				A358EP-K		from 13" to 24" (from 33 to 60 cm)
	Pro-Chisel	3/8				A358LM-N		
	Pro-Chisel	3/8					A363LM-N	
	Semi Chisel	404					B463EP-N	

HOW TO IDENTIFY A CHAIN	K		50		C		K		072		EOM	
									#			
	.325"		.050"		Semi-Chisel		Anti-kickback tooth		N° links reel length		Loop boxes, reels	
	Pitch		Gauge		Tooth type		Anti-kickback protection					
	A	3/8"	50	.050" (1.3 mm)	C	Semi-Chisel	K				EOM	
	B	.404	58	.058" (1.5 mm)	EP	Type "E" professional (Semi-Chisel)	N				EEF	
	E	1/4"	63	.063" (1.6 mm)	LM	Magna Chisel (PRO-CHISEL)					REM	
	K	.325"	43	.043" (1.1 mm)	MC	Micro Chisel						
	N	3/8" Lo Pro			NK	Narrow Kerf						

Accessories for Chainsaws and Pruners - Description of chains



			Electric chainsaws	Petrol chainsaws				Description
				< 35 cc	35 - 45 cc	45 - 60 cc	> 60 cc	
●	●		●	●	●			Recommended for small and medium displacement chainsaws. Clean cut, high performance. Installed on pruner chainsaws.
●			●	●	●			Compact, lightweight and strong. The bar-chain combination offers a weight reduction of around 15% compared to a traditional chain.
●	●		●	●	●			Maximum performance level. Ideal for intensive pruning work.
●			●	●	●			Developed for DIY applications. Guarantees low vibration and maximum safety thanks to the anti-kickback tooth.
	●	●			●	●	●	Lightweight and high performance. This chain was developed for professionals who need an .325" pitch chainsaw.
	●	●			●	●	●	Developed for lightweight chainsaws, guarantees optimal performance and low power absorption.
	●	●			●	●	●	Developed for professional users requiring an .325" pitch chainsaw.
		●			●	●	●	Featuring high performance and strength, this chain is specifically designed for demanding professional applications.
		●			●	●	●	The 3/8 chisel chain has always been the benchmark for professional users.
		●					●	Designed to handle the heaviest duty applications. Unstoppable and super strong.

Pitch	EMAK	OREGON	CARLTON	WINDSOR						
1/4	E650MC-K	25AP	E1MC-BL	50K	90°	30°	.025	85° - 90°	60°	5/32" - 4.0 mm
3/8 LP	N143C-K	90SG	N4C-BL	43RG	90°	35°	.025	85° - 90°	60°	5/32" - 4.0 mm
3/8 LP	N150C-N	91VXL	N1C	50R						
3/8 LP	N150C-K	91VG	N1C-BL	50RG						
.325	K250C-N/K	20BPX	K1C-K1C-BL	50J - 50JG	90°	30°	.025	80° - 90°	60°	3/16" - 4.8 mm
.325	K258C-N/K	21BPX	K2C-K2C-BL	58J - 58JG						
.325	K263C-N	22BPX	K3C	63J - 63JG						
.325	K250NK	95VPX	K1NK-BL	50JSG						
.325	K250L-N	20LPX	K1L	50JL						
.325	K258L-N	21LPX	K2L	58JL	80°	30°	.025	85° - 90°	60°	11/64" - 4.5 mm
.325	K263L-N	22LPX	K3L	63JL						
3/8	A350EP-N	72D - 72DP	A1EP	50A	90°	35°	.025	85° - 90°	60°	7/32" - 5.5 mm
3/8	A358EP-N	73D - 73DP	A2EP	58A						
3/8	A363EP-N	75D - 75DP	A3EP	63A						
3/8	A358EP-K	73V	A2EP-GL							
3/8	A358LM-N	73LGX	A2LM	58APL	80°	30°	.025	80° - 90°	60°	7/32" - 5.5 mm
3/8	A363LM-N	75LGX	A3LM	63APL						

Accessories for Chainsaws and Pruners - Guide-bars and chains



		Guide bars		Chains			Reels Emak 100"		Reels Emak 25"		Efco new references		Machines																						
		Length	Part code	Pitch x gauge	N. links Type	Part code	Type	Part code	N. links Type	Part code	Type	Part code	MT 2200 Li-Ion	MTI 30	MTT 2500	MTT 3600	MT 350 S - MT 3500 S	137 - MT 3700 - MT 371 - MT 3710	137 PS. - MT 3700 PS.	141 S - MT 4100 S - MT 411 - MT 4110	141 SP - MT 4100 SP - MT 411 - MT 4110	MT 440 - MT 4400 - MT 451 - MT 4510	147 - 152 - MT 5200	MTH 510 - MTH 5100 - MTH 560 - MTH 5600	156	162	MT 6500 - MT 6510	MT 7200	MT 2000 E	EP 90 - EP 100 - EP 120 - PTX 2710					
Bar with sprocket nose	PS		16" - cm 41	50180030R	.3/8" x .050" (1,3mm)	56-91 PS	3063006																												
		10" - cm 25	63090031R	.3/8" x .043" (1,1mm)	39-90 SG			N143C-K-100REM	3063037	N143C-K-025REM	3063023	N143C-K-039E	30629529A																						
		12" - cm 30	54050044	.3/8" x .043" (1,1mm)	45-90 PX			N143C-K-100REM	3063037	N143C-K-025REM	3063023	N143C-K-045E	30629541																						
		10" - cm 30	3061025R	.1/4" x .043" (1,1mm)	A4SMB	3062055R																													
		10" - cm 30	3061026R	.1/4" x .043" (1,1mm)	A4SMB	3062055R																													
		10" - cm 25	50290132R	.1/4" x .050" (1,3mm)	58-91 VG			E650MC-K-100REM	3063013	E650MC-K-025REM	3063029A	E650MC-K-058E	30629540A																						
		12" - cm 30	5003 0233R	.3/8" x .050" (1,3mm)	45-91 VG								N150C-K-045E	30629522A																					
													N150C-N-045E	30629518A																					
		14" - cm 35	0935 00357R	.3/8" x .050" (1,3mm)	50-91 VG								N150C-K-050E	30629524A																					
													N150C-N-050E	30629519A																					
		14" - cm 35		.3/8" x .050" (1,3mm)	52-91 VG			N150C-K-100REM	3063022A				N150C-K-052E	30629525A																					
		14" - cm 35	5003 0212R	.3/8" x .050" (1,3mm)	53-91 VG			N150C-N-100REM	3063021A				N150C-N-052E	30629520A																					
													N150C-K-053E	30629526A																					
													N150C-N-055E	30629534A																					
													N150C-K-056E	30629527A																					
													N150C-N-056E	30629535A																					
		16" - cm 41	5005 2019R	.3/8" x .050" (1,3mm)	57-91 VG								N150C-K-057E	30629528A																					
		16" - cm 41	093500536R	.3/8" x .050" (1,3mm)	57-91 VG								N150C-K-057E	30629528A																					
		16" - cm 41	5006 2014R	.325" x .050" (1,3mm)	66-95 VP								K250C-K-066E	30629508A																					
		16" - cm 41	093800067	.325" x .050" (1,3mm)	66-95 VP			K250C-K-100REM	3063015A				K250C-K-066E	30629508A																					
		18" - cm 46	5023 0059R	.325" x .050" (1,3mm)	72-95 VP			K250C-N-100REM	3063014A				K250C-N-025REM	3063030A																					
		18" - cm 46	50310214R	.325" x .050" (1,3mm)	72-95 VP								K250C-K-072E	30629514A																					
		18" - cm 46	50310214R	.325" x .050" (1,3mm)	72-95 VP								K250C-K-072E	30629514A																					
		16" - cm 41	0946 00332R	.325" x .058" (1,5mm)	66-21 BP	001000710R																													
		18" - cm 46	0946 00333R	.325" x .058" (1,5mm)	72-21 BP																														
		20" - cm 51	50012040R	.325" x .058" (1,5mm)	78-21 BP																														
		20" - cm 51	50310215R	.325" x .058" (1,5mm)	78-21 BP																														
		15" - cm 38		.325" x .058" (1,5mm)	64-21 LP																														
		16" - cm 41	5001 2038R	.325" x .058" (1,5mm)	66-21 BP	001000710R																													
		18" - cm 46	5001 2039R	.325" x .058" (1,5mm)	72-21 BP																														
		20" - cm 51	5001 2040R	.325" x .058" (1,5mm)	78-21 BP																														
		18" - cm 46	50092021R *	.3/8" x .058" (1,5mm)	68-73 DP								A358EP-K-068E	30629502A																					
		18" - cm 46	5002 2023R	.3/8" x .058" (1,5mm)	68-73 DP								A358EP-K-068E	30629502A																					
		20" - cm 51	5002 2024R	.3/8" x .058" (1,5mm)	72-73 DP								A358EP-K-072E	30629503A																					
		22" - cm 56	5002 2025*	.3/8" x .058" (1,5mm)	77-73 DP	001000754R*							A358LM-N-072E	30629505*																					
		18" - cm 46	5025 0114R	.3/8" x .058" (1,5mm)	68-73 DP																														
		20" - cm 51	5025 0115R	.3/8" x .058" (1,5mm)	72-73 DP			A358EP-K-100REM	3063009*				A358EP-K-072	30629502A																					
								A358EP-N-100REM	3063008A				A358LM-N-072E	30629503A																					
								A358LM-N-100REM	3063010A																										
		24" - cm 61	5025 0116R	.3/8" x .058" (1,5mm)	84-73 DP																														
		18" - cm 46	50310233R	.3/8" x .058" (1,5mm)	68-73 DP								A358EP-K-068E	30629502A																					
		20" - cm 51	50310234R	.3/8" x .058" (1,5mm)	68-73 DP								A358EP-K-072E	30629502A																					
		20" - cm 51	0970 00301R	.3/8" x .058" (1,5mm)	72-73 DP								A358EP-K-072E	30629503A																					
		25" - cm 64	5002 2042R*	.3/8" x .058" (1,5mm)	88-73 DP								A358LM-N-072E	30629505*																					
													A358EP-K-088E	30629504A																					

(1) Non-European countries only. • Standard cutting systems. ° Compatible cutting systems. PS Power Sharp * While stocks last

Accessories for Chainsaws and Pruners - Guide-bars and chains



	Guide bars		Chains			Reels Emak 100"		Reels Emak 25"		Efco new references		Machines																							
	Length	Part code	Pitch x gauge	N. links Type	Part code	Type	Part code	N. links Type	Part code	Type	Part code	MT 2200 Li-Ion	MTI 30	MTT 2500	MTT 3600	MT 350 S - MT 3500 S	137 - MT 3700 - MT 371 - MT 3710	137 P.S. - MT 3700 P.S.	141 S - MT 4100 S - MT 411 - MT 4110	141 SP - MT 4100 SP - MT 411 - MT 4110	MT 440 - MT 4400 - MT 451 - MT 4510	147 - 152 - MT 5200	MTH 510 - MTH 5100 - MTH 560 - MTH 5600	156	162	MT 6500 - MT 6510	MT 7200	MT 2000 E	EP 90 - EP 100 - EP 120 - PTX 2710						
Bar with stellite nose		10" - cm 25	5003 0353R	.1/4" x .050" (1,3mm)	60-25 AP		E650MC-K-100REM	3063013A	E650MC-K-025REM	3063029A	E650MC-K-060E	30629532A		●																					
		18" - cm 46		.3/8" x .058" (1,5mm)	68-73 DP		A358EP-K-100REM A358EP-N-100REM A358LM-N-100REM	3063009* 3063008A 3063010A	A358LM-N-025REM	3063025*																									
		20" - cm 51		.3/8" x .058" (1,5mm)	72-73 DP							A358EP-K-072E	30629503A																						
												A358LM-N-072E	30629505*																						
		24" - cm 61	5009 0026R*	.3/8" x .058" (1,5mm)	80-73 LP																														
		20" - cm 51	5025 0119R	.3/8" x .058" (1,5mm)	72-73 DP																														
		24" - cm 61	5025 0120R	.3/8" x .058" (1,5mm)	84-73 DP																														
		28" - cm 71	5025 0121R	.3/8" x .058" (1,5mm)	92-73 DP																														
		30" - cm 76	5025 0118R*	.3/8" x .058" (1,5mm)	102-73 DP																														
		18" - cm 46		.3/8" x .058" (1,5mm)	68-73 DP																														
		20" - cm 51	0970 00318R*	.3/8" x .058" (1,5mm)	72-73 DP																														
		25" - cm 64	0970 00293R*	.3/8" x .058" (1,5mm)	88-73 DP																														
		30" - cm 76	0980 00030R*	.3/8" x .058" (1,5mm)	98-73 DP																														

(1) Non-European countries only. • Standard cutting systems. ° Compatible cutting systems. * While stocks last

Supplementary chains	.325" x .063" (1,6mm)	67-22PBX		K263C-N-100REM	3063020A	K263C-N-025REM	3063033*	K263C-N-067E	30629533A
		74-22PBX						K263C-N-074E	30629517A
	.325" x .063" (1,6mm)					K263L-N-025REM	3063034*		
	.3/8" x .063" (1,6mm)	66-75LGX		A363LM-N-100REM	3063012	A363LM-N-025REM	3063027*	A363LM-N-066E	30629511*
		72-75LGX						A363LM-N-072E	30629507*
	.3/8" x .063" (1,6mm)	66-75D-DP		A363EP-N-100REM	3063011A	A363EP-N-025REM		A363EP-N-066E	30629501*
		72-75D-DP						A363EP-N-072E	30629506*
	.3/8" x .050" (1,3mm)	72D-DP		A350EP-N-100REM	3063007A				

Number of chain links in chain roll sizes	Pitch	100" roll	25" roll
	3/8"	1640 links	412 links
	.325"	1848 links	464 links
	.404"	1484 links	372 links
	.1/4"	2392 links	600 links